

|                                              | Ident.-No.        | Euro     |
|----------------------------------------------|-------------------|----------|
| iBED SWING / iBED SWING SafeLight Technology | 271 646 / 272 533 | 27,400.– |
| iBED XTT / iBED XTT SafeLight Technology     | 271 648 / 272 532 | 25,400.– |
| iBED CPS / iBED CPS SafeLight Technology     | 271 647 / 272 534 | 25,400.– |

**OPTIONAL FEATURES**

|                                                                 |                             |         |
|-----------------------------------------------------------------|-----------------------------|---------|
| AROMA                                                           | 271739                      | 1,590.– |
| BREEZE                                                          | 271740                      | 1,790.– |
| Air condition (first equipment)                                 | 271738                      | 1,990.– |
| Exclusive package (AROMA, BREEZE, air condition)                | 272 061                     | 4,500.– |
| SOUNDSYSTEM incl. satellite-speakers, MP3 port and subwoofer    | 271735                      | 1,990.– |
| BINGO                                                           | 271733                      | 790.–   |
| YellowSol for XTT, SWING                                        | 269 307                     | 490.–   |
| YellowSol with LiftLights for CPS                               | 269 308                     | 490.–   |
| EVGs with warm start function and UV-sensor for XTT, SWING, CPS | 272 131 / 272 129 / 272 132 | 2,490.– |
| Exhaust channel platin silver                                   | 264 990                     | 590.–   |
| Thermostatically controlled warm air recirculation              | 272019                      | 290.–   |
| Installation and set-up                                         | 247 171                     | 990.–   |

**TECHNICAL SPECIFICATIONS**

|                                                             |                                                           |
|-------------------------------------------------------------|-----------------------------------------------------------|
| Canopy configuration SWING                                  | 25 x 160 W, 5 x 180 W, 9 x 250 W POWERSPOT                |
| Canopy configuration XTT                                    | 25 x 160 W, 5 x 180 W, 3 x 1000 W XTT                     |
| Canopy configuration CPS                                    | 24 x 180 W, 39 x U-P-P 25 W                               |
| Shoulder tanner configuration SWING, XTT                    | 2 x 250 W POWERSPOT                                       |
| Bench configuration                                         | 20 x 160 W                                                |
| Size L x D x H (closed canopy; depth incl. exhaust channel) | 238 x 163 x 159 cm                                        |
| Size L x D x H (open canopy)                                | 238 x 149 x 201 cm                                        |
| Height inclusive exhaust channel                            | 232 cm                                                    |
| Minimum cubicle size recommended                            | 250 x 250 cm                                              |
| Hose diameter of exhaust channel                            | 300 mm                                                    |
| Minimum air discharge rate                                  | 2300 m <sup>3</sup> /h                                    |
| Weight                                                      | approx. 850 kg                                            |
| Power consumption (incl. air condition)                     | XTT: 13.3 kW; CPS:11.8 kW; SWING: 14.4 kW                 |
| Electrical connection                                       | 400 V 3 N-PE 50 Hz                                        |
| Fuse protection                                             | 3 x 32 A (K32)                                            |
| Design / Colour                                             | snow metallic/graphit metallic, snow metallic/loop orange |



- High pressure (XTT, SWING) or low pressure (CPS) facial tanner
- Separate adjustment of tanning intensity for face and body
- Switch-off facial tanner
- POWERSPOT shoulder tanner (XTT/SWING)
- Separate adjustment of ventilation for face and body
- MP3 sound
- LeXtra leg tanners
- LIGHTGLASS
- XXL body-shaped lounge bench
- Integrated service module
- BREAKSAFE
- Remote start device
- Standby light
- FLOORLIGHT
- Effect finish colours
- GS approved
- CE mark
- Meets the RTS-criteria certified tanning unit