

	Ident.-No.	Euro
LOTUS XTT (100/100) / (100/100) SafeLight Technology	273 443 / 273 397	13,900.-
LOTUS XTT (100/160) / (100/160) SafeLight Technology	273 442 / 273 396	14,500.-
LOTUS XTT (160/160) / (160/160) SafeLight Technology	273 441 / 273 242	14,900.-
LOTUS CPS (100/120) / (100/120) SafeLight Technology	273 461 / 273 400	13,900.-
LOTUS CPS (100/180) / (100/180) SafeLight Technology	273 460 / 273 399	14,500.-
LOTUS CPS (160/180) / (160/180) SafeLight Technology	273 459 / 273 398	14,900.-

OPTIONAL FEATURES

Air condition (first equipment)	268 404	1,990.-
Air condition (upgrade kit)	265 847	2,190.-
LIGHTGLASS XTT / CPS	265 838 / 266 526	390.-
Exhaust channel platin silver	264 990	590.-
Thermostatically controlled warm air recirculation	266 525	290.-
Installation and set-up	247 171	990.-

TECHNICAL SPECIFICATIONS

Canopy configuration XTT	20 x 100 W, 3 x 400 W or 20 x 160 W, 3 x 400 W
Canopy configuration CPS	20 x 120 W, 30 x U-P-P 25 W or 20 x 180 W, 30 x U-P-P 25 W
Bench configuration	16 x 100 W or 16 x 160 W
Size L x D x H (closed canopy; depth incl. exhaust channel)	228 x 134 x 139 cm
Size L x D x H (open canopy)	228 x 134 x 171 cm
Height inclusive exhaust channel	200 cm
Minimum cubicle size recommended	240 x 220 cm
Connection of exhaust channel	leading up to ceiling
Hose diameter of exhaust channel	300 mm
Minimum air discharge rate	1500 m ³ /h
Weight	approx. 500 kg
Electrical connection	400 V 3 N-PE 50 Hz
Power consumption (incl. air condition)	max. 12 kW
Fuse protection	XTT (100/100), CPS (100/120): 3 x 16 A (K16)
	XTT (100/160), CPS (100/180): 3 x 16 A (K16)
	XTT (160/160), CPS (160/180): 3 x 25 A (K25)
Design / Colour	platin silver



- Low pressure CPS or high pressure XTT facial tanner
- Adjustable facial tanner
- Common adjustment of ventilation for face and body
- Switch-off facial tanner
- MP3 sound
- LeXtra leg tanners ?lamp technology?
- Integrated service module
- BREAKSAFE
- Remote start device
- AIR CONDITION Vorrichtung
- Easy-touch canopy lift
- Standby light
- FLOORLIGHT
- GS approved
- CE mark
- Meets the RTS-criteria certified tanning unit

LOTUS ZEN



- Low pressure CPS or high pressure XTT facial tanner
- Adjustable facial tanner
- Common adjustment of ventilation for face and body
- Switch-off facial tanner
- MP3 sound
- LeXtra leg tanners
- Integrated service module
- BREAKSAFE
- Remote start device
- AIR CONDITION *Vorrichtung*
- Easy-touch canopy lift
- Standby light
- FLOORLIGHT
- GS approved
- CE mark
- Meets the RTS-criteria certified tanning unit

Ident-No.

Euro

	Ident-No.	Euro
LOTUS ZEN XTT (100/100) / (100/100) SafeLight Technology	273 484 / 273 493	14,900.–
LOTUS ZEN XTT (100/160) / (100/160) SafeLight Technology	273 485 / 273 494	15,400.–
LOTUS ZEN XTT (160/160) / (160/160) SafeLight Technology	273 486 / 273 495	15,900.–
LOTUS ZEN CPS (100/120) / (100/120) SafeLight Technology	273 487 / 273 490	14,900.–
LOTUS ZEN CPS (100/180) / (100/180) SafeLight Technology	273 488 / 273 491	15,400.–
LOTUS ZEN CPS (160/180) / (160/180) SafeLight Technology	273 489 / 273 492	15,900.–

OPTIONAL FEATURES

Air condition (first equipment)	268 404	1,990.–
Air condition (upgrade kit)	265 847	2,190.–
LIGHTGLASS XTT/CPS	265 838 / 266 526	390.–
Exhaust channel platin silver	264 990	590.–
Thermostatically controlled warm air recirculation	266 525	290.–
Installation and set-up	247 171	990.–

TECHNICAL SPECIFICATIONS

Canopy configuration XTT	20 x 100 W, 3 x 400 W or 20 x 160 W, 3 x 400 W
Canopy configuration CPS	20 x 120 W, 30 x 25 W U-P-P or 20 x 180 W, 30 x 25 W U-P-P
Bench configuration	16 x 100 W or 16 x 160 W
Size L x D x H (closed canopy; depth incl. exhaust channel)	228 x 134 x 139 cm
Size L x D x H (open canopy)	228 x 134 x 171 cm
Height inclusive exhaust channel	200 cm
Minimum cubicle size recommended	240 x 220 cm
Connection of exhaust channel	leading up to ceiling
Hose diameter of exhaust channel	300 mm
Minimum air discharge rate	1500 m ³ /h
Weight	approx. 500 kg
Power consumption (incl. air condition)	max. 12 kW
Electrical connection	400 V 3 N-PE 50 Hz
Fuse protection	XTT (100/100), XTT (100/160), CPS (100/180), CPS (100/120): 3 x 16 A (K16) XTT (160/160), CPS (160/180): 3 x 25 A (K25)
Design / Colour	transluminescent