



- XTT high pressure technology in the canopy, low pressure technology or comfortable mattress in the bench
- Separate adjustment of tanning intensity for face and body
- Disengageable facial tanner
- POWERSPOT shoulder tanner
- MP3 sound
- High-performance body- and facial fan, twistable facial fan
- Separate adjustment of ventilation for face and body
- Quadruple BREEZE
- AROMA
- AIR CONDITION (not for P90 MATTRESS)
- LIGHTGLASS
- XXL bench
- Integrated service module
- BREAKSAFE
- Remote start device
- Easy-touch canopy lift
- Thermostatically controlled warm air recirculation
- Exhaust channel platin silver
- Standby-Licht
- FLOORLIGHT
- Effect light
- Effect finish colours
- GS approved
- CE mark
- Meets the RTS-criteria certified tanning unit

P90

	Ident-No.	Euro
P90 COMBO / P90 COMBO SafeLight Technology	268 401 / 272 572	38,400.-
P90 MATTRESS / P90 MATTRESS SafeLight Technology	268 400 / 272 573	38,400.-
P90 HIGH PRESSURE		41,900.-
OPTIONAL FEATURES		
Installation and set-up	247 171	990.-
TECHNICAL SPECIFICATIONS		
Canopy configuration	12 x 600 W, 3 x 1000 W XTT	
Canopy configuration P90 MATTRESS	12 x 600 W, 3 x 1000 W XTT	
Bench configuration	20 x 160 W or 24 x 400 W XTT	
Base specification P90 MATTRESS	UV-resistant comfort mattress	
Shoulder tanner configuration	2 x 250 W POWERSPOT	
Size L x D x H (closed canopy; depth incl. exhaust channel)	250 x 165 x 185 cm	
Size L x D x H (open canopy)	250 x 165 x 200 cm	
Height inclusive exhaust channel	237 cm	
Minimum cubicle size recommended	260 x 250 cm	
Connection of exhaust channel	at the rear leading up to ceiling	
Hose diameter of exhaust channel	300 mm	
Minimum air discharge rate	3000 m ³ /h	
Weight	approx. 775 kg	
Power consumption P90 (incl. air condition)	17.6 kW	
Power consumption P90 MATTRESS	12.9 kW	
Electrical connection	400 V 3 N-PE 50 Hz	
Fuse protection	3 x 32 A (K32)	
Design / Colour	snow metallic/platin silver	